



## SolarEdge Single Phase Inverters-16A

SE3000(\*) (\*\*) / SE3500(\*) (\*\*) / SE4000-16A



INVERTERS

### Specifically designed to work with power optimizers

- Superior efficiency (97.6%)
- Small, lightweight and easy to install
- Built-in module-level monitoring
- Internet connection through Ethernet or Wireless
- IP65 – Outdoor and indoor installation
- Fixed voltage inverter, DC/AC conversion only



# Single Phase Inverters - 16A

SE3000(\*) (\*\*) / SE3500(\*) (\*\*) / SE4000-16A

	SE3000(*) (**)	SE3500(*) (**)	SE4000-16A	
<b>OUTPUT</b>				
Rated AC Power Output	3000	3500	4000	VA
Maximum AC Power Output	3000	3500	4000	VA
AC Output Voltage (Nominal)		220 / 230		Vac
AC Output Voltage Range		184 - 264.5		Vac
AC Frequency (Nominal)		50 / 60 ± 5		Hz
Maximum Continuous Output Current		16		A
Residual Current Detector / Residual Current Step Detector		300 / 30		mA
Utility Monitoring, Islanding Protection, Country Configurable Thresholds		Yes		
<b>INPUT</b>				
Recommended Maximum DC Power*** (Module STC)	3300	3900	4400	W
Transformer-less, Ungrounded		Yes		
Maximum Input Voltage		500		Vdc
Nominal DC Input Voltage		350		Vdc
Maximum Input Current	11.5	13.5	15.5	Adc
Reverse-Polarity Protection		Yes		
Ground-Fault Isolation Detection		600k $\Omega$ Sensitivity		
Maximum Inverter Efficiency		97.6		%
European Weighted Efficiency		97.5		%
Nighttime Power Consumption		< 2.5		W
<b>ADDITIONAL FEATURES</b>				
Supported Communication Interfaces		RS485, RS232, Ethernet, Zigbee (optional)		
<b>STANDARD COMPLIANCE</b>				
Safety		IEC-62103 (EN50178), IEC-62109		
Grid Connection Standards		VDE 0126-1-1, VDE-AR-N-4105, AS-4777, RD-1663, DK 5940		
Emissions		IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12, FCC part15 class B		
RoHS		Yes		
<b>INSTALLATION SPECIFICATIONS</b>				
AC Output		Cable Gland - diameter 9-16		mm
DC Input		1 MC4 pair	2 MC4 pairs	
Dimensions (HxWxD)		540 x 315 x 172	540 x 315 x 191	mm
Weight		20.2	21.7	kg
Cooling		Natural Convection		
Noise		< 50		dBA
Operating Temperature Range		-20 - +50 (M40 version -40 - +50)		°C
Protection Rating		IP65 - Outdoor and Indoor		
Bracket Mounted (Bracket Provided)				

\* SE3000-GBR & SE3500-GBR for United Kingdom.

\*\* SE3000 & SE3500 for Denmark, Portugal, Poland should be set to countrycode DEN, PRT or POL respectively to limit to 16A. For other countries contact SolarEdge.

\*\*\* Higher input DC power may be installed; analyze yearly AC performance.



© SolarEdge Technologies, Inc. All rights reserved. SOLAREEDGE, the SolarEdge logo, OPTIMIZED BY SOLAREEDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc. All other trademarks mentioned herein are trademarks of their respective owners. Date: 03/2013. Subject to change without notice.



www.real-solar.com